


## Non-Insulated Spade Terminal Dimensions



Wire Range (AWG)	Wire Range (mm <sup>2</sup> )	Stud Size (in.)	Stud Size (mm)	Dimensions (in.)				Dimensions (mm)				Cat. No.
				L	W	E	F	L	W	E	F	
22-18	0.5 - 1.0	6	3.7	.630	.252	.189	.256	16.0	6.4	4.8	6.5	<b>83-6111</b>
		8	4.3	.630	.283	.189	.256	16.0	7.2	4.8	6.5	<b>83-6121</b>
		10	5.3	.630	.319	.189	.256	16.0	8.1	4.8	6.5	<b>83-6131</b>
16-14	1.5 - 2.5	8	4.3	.630	.283	.189	.256	16.0	7.2	4.8	6.5	<b>83-6161</b>
		10	5.3	.630	.366	.189	.256	16.0	9.3	4.8	6.5	<b>83-6171</b> <b>84-6171</b>
12 - 10	4.0 - 6.0	8	4.3	.728	.354	.236	.276	18.5	9.0	6.0	7.0	<b>83-6211</b>
		10	5.3	.728	.354	.236	.276	18.5	9.0	6.0	7.0	<b>83-6221</b>
		1/4	6.4	.965	.472	.236	.472	24.5	12.0	6.0	12.0	<b>83-6231</b>

105°C/600 Volts max.