




In-Sure™ Push-In Wire Connectors


- *High quality, secure connections*
- *Clear shell gives visual verification of connection*
- *Ergonomic design for easy grip and comfort*
- *Low insertion force for fast connections*
- *Fits any combination of #12-18 AWG solid and stranded copper wires*



*Easily Accepts
Stranded or Solid Wire*

A circular inset image showing a close-up of a person's hand holding a red In-Sure connector. A copper wire is being inserted into the top of the connector. The wire is partially inserted, and the clear plastic shell of the connector is visible, showing the internal contacts.

Available in 2, 3 and 4 port models
(6 port model available soon)





In-Sure™ Push-In Wire Connectors



If it's IDEAL, it's a quality connector – and the In-Sure™ Push-In Wire Connector is no exception. Color-coded, the clear polycarbonate housing allows for visual verification of every connection. The ergonomic design of the In-Sure is easier to grip which means more comfortable push-in connections. Perfect for OEM lighting manufacturing, prefabricated wiring systems and other OEM and branch circuit wiring applications. Simply push the wire in – the low insertion force makes it easy. UL Listed, CSA Certified and rated to 600V and 105C. In-Sure saves time and improves productivity while perfecting connections.

Great for residential applications as well.


Color-coded for easy identification




Tin-plated copper bus system

Stainless steel inserts restrict pull-out

Check port for continuity testing


Visual verification of connection



12-18 AWG Models	Color	No. of Ports	Length		Width		Height		Quantity	Cat. No.	
			mm	in.	mm	in.	mm	in.			
	32	Red	2	19.81	0.78	13.21	0.52	9.65	0.38	Box of 100	30-1032
										Jar of 300	30-1032J
										Box of 5000	30-1632
	33	Orange	3	19.81	0.78	17.53	0.69	9.65	0.38	Box of 100	30-1033
										Jar of 250	30-1033J
										Box of 5000	30-1633
	34	Yellow	4	19.81	0.78	20.83	0.82	9.65	0.38	Box of 100	30-1034
										Jar of 200	30-1034J
										Box of 5000	30-1634

(6 port model available soon)

10-14 AWG Model

	39	Blue	3	19.81	0.78	21.84	0.86	11.43	0.45	Box of 50	30-1039
										Jar of 150	30-1039J
										Box of 2500	30-1639

COPPER TO COPPER ONLY. Do not use on aluminum.
 Temperature rating: 105°C (221°F) maximum
 600V maximum building wire, 1000V maximum signs or lighting fixtures

Models 32, 33, 34 Wire Combination Range

Solid	#20 – #12 solid
Stranded	#16 – #12 (19 strand or less) #18 (7 strand)
Stranded Tin-Bonded	#18 – #14 (19 strand or less)

Model 39 Wire Combination Range

Solid	#14 – #10 solid
Stranded	#12 – #10 (19 strand or less)
Stranded Tin-Bonded	#14 – #10 (19 strand or less)



IDEAL INDUSTRIES, INC.
 Becker Place, Sycamore, IL 60178, USA / 815-895-5181 • 800-435-0705 in USA

International offices: Australia • Brazil • Canada • China • Germany • Mexico • UK
 For complete sales office contact information, visit us at:
www.idealindustries.com

Rev. 2/09
 Form No. P-2854
 Printed in USA
 ©2008 IDEAL INDUSTRIES, INC.