



CLEARGLIDE® AEROSOL

WIRE PULLING LUBRICANT

NEW
AEROSOL
LUBRICANT



IDEAL electrical

Directions

1. Show the label.
2. Insert the nozzle.
3. Dispense lubricant.
4. Remove nozzle and cap.
5. Begin pulling wire with lubricant in use.

Content: Polyethylene Glycol

1-387

Distributed by IDEAL INDUSTRIAL, INC.
1275 Park Avenue, Suite 100
Cincinnati, OH 45202

Made in U.S.A.

MADE IN

USA

CLEARGLIDE® AEROSOL

WIRE PULLING LUBRICANT

Elevate your electrical installations with our foam wire pulling lubricants. Designed specifically for electricians, our advanced formula reduces mess, offers 4x the yield, and is crafted with our trusted 20-year-old ClearGlide technology. Enjoy faster, cleaner, and more efficient pulls, saving you time and effort on every job. Experience superior performance and reliability, making your work smoother and more professional. Choose the best and see the difference in your projects.

- Shake well before use (one minute is recommended)
- Foam lubricant applies to conduit quick and easy — great for indoor and retrofit pulls.
- Foaming fills conduit sizes up to 1-1/2 inches
- Insert tube 4-6 inches inside conduit
- No stains to fabric or hands when washed thoroughly
- Same great performance as our standard ClearGlide® formula
- Our proprietary formula is suitable for all electrical and datacom applications and is safe to use with all cable types.
- Foam lubricant evaporates in conduit, leaves behind a thin layer of non-conductive film that won't clog conduit
- Remains stable over wide temperature ranges — usable from 32°F to 122°F (0°C to 50°C)
- If product freezes, must return to room temperature before use



Reduced Mess

Foam lubricants are less messy compared to gel or liquid lubricants. This minimize cleanup time, keeps the work area clean and enhances overall efficiency.



Compatibility with Various Cables

This versatility makes them suitable for different projects, providing flexibility for the electrician.

The Full-Line of ClearGlide® Wire Pulling Lubricant

Our family of ClearGlide® has offerings in a 19-Ounce Aerosol Can, 1-Quart Bottle, 1-Gallon bucket and 5-Gallon Bucket.

Description	Part No.	UPC
1-Qt. Squeeze Bottle	31-388	783250348152
1-Gal. Bucket	31-381	783250348145
5-Gal. Bucket	31-385	783250440009
19-Oz. Spray Can	31-387	783250200573



Ease of Application

Actuator and tube system provide precise application control, allowing for a consistent spray pattern reducing product waste.

Sleek Aerosol Can

Space savings up to 10% in your tool bag. ClearGlide aerosol is 100% recyclable and is corrosion resistance.

High Yield

Aerosol can provides a higher yield, meaning more pulls per container, resulting in a cost saving.



For frequently asked questions,
SCAN HERE

**Must wash hand with soap, and wash clothes with standard detergents to prevent stains
**When applied vertically, insert 4-6 in., hold spray button for 2-3 second and begin pulling for best results.*



IDEAL INDUSTRIES, INC.
1375 Park Avenue, Sycamore, IL 60178, USA / 815-895-5181 • 800-435-0705 in USA
For complete sales office contact information, visit us at: idealind.com

Form No. P-6087
©2025 IDEAL INDUSTRIES, INC.
PRINTED IN USA
6/25

LUBRICANT COMPARISON CHART

FAQ'S